




塑料外壳双面金属化聚丙烯膜电容器

Double sided metallized polypropylene film capacitor (Box-type)

■ 外形图 Outline Drawing



■ 特点

- 双面金属化聚丙烯引出
- 损耗小，内部温升小
- 负电容量温度系数
- 优异的阻燃性能

■ Features

- Doublesided metallized polypropylene structure
- Low loss and small inherent temperature rise
- Negative temperature coefficient of capacitance
- Excellent active and passive flame resistant circuit

■ 主要用途

- 广泛应用于高压高频脉冲电路中
- 电视机中S校正和行逆程波形和显示器中
- 电子镇流器和节能灯中
- 吸收和SCR整流电路

■ Typical Applications

- widely used in high voltage, high frequency and pulse circuit
- Deflection circuits in TV-sets(S-correction and fly-back tuning)and monitors
- Lamp capacitor for electronic ballast and compact lamps
- SNUBBER and SCR commutating circuits

■ 技术要求 Specifications

引用标准 Reference Standard	GB/T 10190 (IEC 60384-16)
气候类别 Climatic Category	40/105/56
额定温度 Rated Temperature	85℃ for V_R (dc); 75℃ for V_R (ac)
工作温度范围 Operating Temperature Range	-40℃~105℃ (+85℃ to +105℃: decreasing factor 1.25% per °C for V_R (dc)) (+75℃ to +105℃: decreasing factor 1.35% per °C for V_R (ac))
额定电压 Rated Voltage	250V, 400V, 630V, 1 000V, 1 600V, 2 000V
电容量范围 Capacitance Range	0.00022μF~3.9μF
电容量偏差 Capacitance Tolerance	± 2%(G), ± 3%(H), ± 5%(J), ± 10%(K), ± 20%(M)
耐电压 Voltage Proof	1.60 U_R (5s)
损耗角正切 Dissipation Factor	≤ 0.0010 (1kHz, 20℃)
绝缘电阻 Insulation Resistance	≥ 50 000MΩ C_R ≤0.33μF ≥ 15 000s C_R >0.33μF (20℃, 100V, 1min)

产品编码说明 Part number system

■ 18位产品代码如下:

The 18 digits part number is formed as follow:

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
C	8	2															

第1~3位	薄膜电容器系列代码 C82= MMKP82	Digit 1 to 3	Series code of film capacitor C82= MMKP82
第4~5位	直流额定电压 2E=250V 2G=400V 2J=630V 3A=1000V 3C=1600V 3D=2000V	Digit 4 to 5	DC rated voltage 2E=250V 2G=400V 2J=630V 3A=1000V 3C=1600V 3D=2000V
第6~8位	标称容量 举例: 103=10 × 10 ³ pF=0.01μF	Digit 6 to 8	Rated capacitance value For example: 103=10 × 10 ³ pF=0.01μF
第9位	容量偏差 G= ± 2%, H= ± 3%, J= ± 5% K= ± 10%, M= ± 20%	Digit 9	Capacitance tolerance G= ± 2%, H= ± 3%, J= ± 5% K= ± 10%, M= ± 20%
第10位	引线脚距 P 3=7.5mm 4=10.0mm 6=15.0mm 9=22.5mm B=27.5mm	Digit 10	Pitch 3=7.5mm 4=10.0mm 6=15.0mm 9=22.5mm B=27.5mm
第11位	内部特征码	Digit 11	Internal use
第12~15位	引线加工和包装代码	Digit 12 to 15	Lead form and packaging code
第16~18位	内部特征码	Digit 16 to 18	Internal use

■ Table1 引线加工和包装代码 Lead form and packaging code

第12位 Digit 12		第13位 Digit 13		第14位 Digit 14		第15位 Digit 15	
代码 Code	说明 explanation	代码 Code	说明 explanation	代码 Code	说明 explanation	代码 Code	说明 explanation
A	弹带包装 ammo-pack	3	F=7.5mm	0	表示直脚 straight	1	产品在连续的两个载带孔之间 each cap. among two consecutive holes P3=12.7mm,H=18.5mm (For pitch=7.5mm)
		4 6	F=10.0mm F=15.0mm			5	P3=25.4mm,H=18.5mm (For pitch=10/15mm) (Detail parameter refer to pag 15)
C	直脚 straight lead “C” in the figure above	代码 Code	说明 explanation			0	引线长度偏差±0.5mm或标准长度 Length tolerance ±0.5mm Or standard length
		00	标准的引线长度(18mm~26mm) standard lead length				
		45	引线长度 4.5mm lead length 4.5mm				



■ 外形尺寸 Dimensions(mm)

250Vdc(180Vac)						
容量 (μ F)	W	H	T	P	d	产品代码 Part number
0.0068	10.5	9.0	4.0	7.5	0.6	C822E682-30****+++
0.0082	10.5	9.0	4.0	7.5	0.6	C822E822-30****+++
0.010	10.5	9.0	4.0	7.5	0.6	C822E103-30****+++
0.012	10.5	9.0	4.0	7.5	0.6	C822E123-30****+++
0.015	10.5	9.0	4.0	7.5	0.6	C822E153-30****+++
0.018	10.5	9.0	4.0	7.5	0.6	C822E183-30****+++
0.022	10.5	9.0	4.0	7.5	0.6	C822E223-30****+++
0.027	10.5	11.0	5.0	7.5	0.6	C822E273-30****+++
0.033	10.5	11.0	5.0	7.5	0.6	C822E333-30****+++
0.039	10.5	12.0	6.0	7.5	0.6	C822E393-30****+++
0.047	10.5	12.0	6.0	7.5	0.6	C822E473-30****+++
0.027	13.0	9.0	4.0	10.0	0.6	C822E273-40****+++
0.033	13.0	9.0	4.0	10.0	0.6	C822E333-40****+++
0.039	13.0	9.0	4.0	10.0	0.6	C822E393-40****+++
0.047	13.0	11.0	5.0	10.0	0.6	C822E473-40****+++
0.056	13.0	11.0	5.0	10.0	0.6	C822E563-40****+++
0.068	13.0	12.0	6.0	10.0	0.6	C822E683-40****+++
0.082	13.0	12.0	6.0	10.0	0.6	C822E823-40****+++
0.068	17.5	11.0	5.0	15.0	0.8	C822E683-60****+++
0.082	17.5	11.0	5.0	15.0	0.8	C822E823-60****+++
0.10	17.5	11.0	5.0	15.0	0.8	C822E104-60****+++
0.12	17.5	12.0	6.0	15.0	0.8	C822E124-60****+++
0.15	17.5	12.0	6.0	15.0	0.8	C822E154-60****+++
0.18	17.5	13.5	7.5	15.0	0.8	C822E184-60****+++
0.22	17.5	13.5	7.5	15.0	0.8	C822E224-60****+++
0.27	17.5	14.5	8.5	15.0	0.8	C822E274-60****+++
0.33	17.5	16.0	10.0	15.0	0.8	C822E334-60****+++
0.39	17.5	16.0	10.0	15.0	0.8	C822E394-60****+++
0.22	26.5	15.0	6.0	22.5	0.8	C822E224-90****+++
0.27	26.5	15.0	6.0	22.5	0.8	C822E274-90****+++
0.33	26.5	15.0	6.0	22.5	0.8	C822E334-90****+++
0.39	26.5	16.0	7.0	22.5	0.8	C822E394-90****+++
0.47	26.5	16.0	7.0	22.5	0.8	C822E474-90****+++
0.56	26.5	17.0	8.5	22.5	0.8	C822E564-90****+++
0.68	26.5	18.5	10.0	22.5	0.8	C822E684-90****+++
0.82	26.5	18.5	10.0	22.5	0.8	C822E824-90****+++
1.0	26.5	22.0	12.0	22.5	0.8	C822E105-90****+++
0.82	32.0	18.0	9.0	27.5	0.8	C822E824-B0****+++
1.0	32.0	20.0	11.0	27.5	0.8	C822E105-B0****+++
1.2	32.0	20.0	11.0	27.5	0.8	C822E125-B0****+++
1.5	32.0	22.0	13.0	27.5	0.8	C822E155-B0****+++
1.8	32.0	24.5	15.0	27.5	0.8	C822E185-B0****+++
2.2	32.0	24.5	15.0	27.5	0.8	C822E225-B0****+++
2.7	32.0	33.0	18.0	27.5	0.8	C822E275-B0****+++
3.3	32.0	33.0	18.0	27.5	0.8	C822E335-B0****+++
3.9	32.0	33.0	18.0	27.5	0.8	C822E395-B0****+++

400Vdc(250Vac)@						
容量 (μ F)	W	H	T	P	d	产品代码 Part number
0.0027	10.5	9.0	4.0	7.5	0.6	C822G272-30****+++
0.0033	10.5	9.0	4.0	7.5	0.6	C822G332-30****+++
0.0039	10.5	9.0	4.0	7.5	0.6	C822G392-30****+++
0.0047	10.5	9.0	4.0	7.5	0.6	C822G472-30****+++
0.0056	10.5	9.0	4.0	7.5	0.6	C822G562-30****+++
0.0068	10.5	9.0	4.0	7.5	0.6	C822G682-30****+++
0.0082	10.5	9.0	4.0	7.5	0.6	C822G822-30****+++
0.010	10.5	9.0	4.0	7.5	0.6	C822G103-30****+++
0.012	10.5	9.0	4.0	7.5	0.6	C822G123-30****+++
0.015	10.5	11.0	5.0	7.5	0.6	C822G153-30****+++
0.018	10.5	11.0	5.0	7.5	0.6	C822G183-30****+++
0.022	10.5	12.0	6.0	7.5	0.6	C822G223-30****+++
0.027	10.5	12.0	6.0	7.5	0.6	C822G273-30****+++
0.010	13.0	9.0	4.0	10.0	0.6	C822G103-40****+++
0.012	13.0	9.0	4.0	10.0	0.6	C822G123-40****+++
0.015	13.0	9.0	4.0	10.0	0.6	C822G153-40****+++
0.018	13.0	9.0	4.0	10.0	0.6	C822G183-40****+++
0.022	13.0	9.0	4.0	10.0	0.6	C822G223-40****+++
0.027	13.0	11.0	5.0	10.0	0.6	C822G273-40****+++
0.033	13.0	11.0	5.0	10.0	0.6	C822G333-40****+++
0.039	13.0	12.0	6.0	10.0	0.6	C822G393-40****+++
0.047	13.0	12.0	6.0	10.0	0.6	C822G473-40****+++
0.033	17.5	11.0	5.0	15.0	0.8	C822G333-60****+++
0.039	17.5	11.0	5.0	15.0	0.8	C822G393-60****+++
0.047	17.5	11.0	5.0	15.0	0.8	C822G473-60****+++
0.056	17.5	11.0	5.0	15.0	0.8	C822G563-60****+++
0.068	17.5	12.0	6.0	15.0	0.8	C822G683-60****+++
0.082	17.5	12.0	6.0	15.0	0.8	C822G823-60****+++
0.10	17.5	13.5	7.5	15.0	0.8	C822G104-60****+++
0.12	17.5	13.5	7.5	15.0	0.8	C822G124-60****+++
0.15	17.5	14.5	8.5	15.0	0.8	C822G154-60****+++
0.18	17.5	16.0	10.0	15.0	0.8	C822G184-60****+++
0.22	17.5	16.0	10.0	15.0	0.8	C822G224-60****+++
0.27	17.5	19.0	11.0	15.0	0.8	C822G274-60****+++
0.12	26.5	15.0	6.0	22.5	0.8	C822G124-90****+++
0.15	26.5	15.0	6.0	22.5	0.8	C822G154-90****+++
0.18	26.5	15.0	6.0	22.5	0.8	C822G184-90****+++
0.22	26.5	16.0	7.0	22.5	0.8	C822G224-90****+++
0.27	26.5	17.0	8.5	22.5	0.8	C822G274-90****+++
0.33	26.5	17.0	8.5	22.5	0.8	C822G334-90****+++
0.39	26.5	18.5	10.0	22.5	0.8	C822G394-90****+++
0.47	26.5	18.5	10.0	22.5	0.8	C822G474-90****+++
0.56	26.5	22.0	12.0	22.5	0.8	C822G564-90****+++
0.68	26.5	22.0	12.0	22.5	0.8	C822G684-90****+++
0.39	32.0	18.0	9.0	27.5	0.8	C822G394-B0****+++
0.47	32.0	18.0	9.0	27.5	0.8	C822G474-B0****+++
0.56	32.0	20.0	11.0	27.5	0.8	C822G564-B0****+++
0.68	32.0	20.0	11.0	27.5	0.8	C822G684-B0****+++
0.82	32.0	22.0	13.0	27.5	0.8	C822G824-B0****+++
1.0	32.0	24.5	15.0	27.5	0.8	C822G105-B0****+++
1.2	32.0	24.5	15.0	27.5	0.8	C822G125-B0****+++
1.5	32.0	33.0	18.0	27.5	0.8	C822G155-B0****+++
1.8	32.0	33.0	18.0	27.5	0.8	C822G185-B0****+++

备注: 1. “-”表示容量偏差。“-”=capacitance tolerance code, M= $\pm 20\%$, K= $\pm 10\%$, J= $\pm 5\%$, H= $\pm 3\%$, G= $\pm 2\%$
 2. “****”表示引线加工和包装代码(见表1)。“****”=lead form and packaging code(refer to table 1)
 3. “@”不用作跨线, 请参见抗干扰电容器(Pag.120)
 “@” Not suitable for across-the-line applications. Pls refer to Interference Suppression Capacitors(Pag. 120)



■ 外形尺寸 Dimensions(mm)

630Vdc(400Vac)						
容量 (μ F)	W	H	T	P	d	产品代码 Part number
0.00068	10.5	9.0	4.0	7.5	0.6	C822J681-30****+++
0.00082	10.5	9.0	4.0	7.5	0.6	C822J821-30****+++
0.0010	10.5	9.0	4.0	7.5	0.6	C822J102-30****+++
0.0012	10.5	9.0	4.0	7.5	0.6	C822J122-30****+++
0.0015	10.5	9.0	4.0	7.5	0.6	C822J152-30****+++
0.0018	10.5	9.0	4.0	7.5	0.6	C822J182-30****+++
0.0022	10.5	9.0	4.0	7.5	0.6	C822J222-30****+++
0.0027	10.5	9.0	4.0	7.5	0.6	C822J272-30****+++
0.0033	10.5	9.0	4.0	7.5	0.6	C822J332-30****+++
0.0039	10.5	9.0	4.0	7.5	0.6	C822J392-30****+++
0.0047	10.5	9.0	4.0	7.5	0.6	C822J472-30****+++
0.0056	10.5	9.0	4.0	7.5	0.6	C822J562-30****+++
0.0068	10.5	11.0	5.0	7.5	0.6	C822J682-30****+++
0.0082	10.5	11.0	5.0	7.5	0.6	C822J822-30****+++
0.010	10.5	12.0	6.0	7.5	0.6	C822J103-30****+++
0.012	10.5	12.0	6.0	7.5	0.6	C822J123-30****+++
0.0039	13.0	9.0	4.0	10.0	0.6	C822J392-40****+++
0.0047	13.0	9.0	4.0	10.0	0.6	C822J472-40****+++
0.0056	13.0	9.0	4.0	10.0	0.6	C822J562-40****+++
0.0068	13.0	9.0	4.0	10.0	0.6	C822J682-40****+++
0.0082	13.0	9.0	4.0	10.0	0.6	C822J822-40****+++
0.010	13.0	11.0	5.0	10.0	0.6	C822J103-40****+++
0.012	13.0	11.0	5.0	10.0	0.6	C822J123-40****+++
0.015	13.0	12.0	6.0	10.0	0.6	C822J153-40****+++
0.018	13.0	12.0	6.0	10.0	0.6	C822J183-40****+++
0.010	17.5	11.0	5.0	15.0	0.8	C822J103-60****+++
0.012	17.5	11.0	5.0	15.0	0.8	C822J123-60****+++
0.015	17.5	11.0	5.0	15.0	0.8	C822J153-60****+++
0.018	17.5	11.0	5.0	15.0	0.8	C822J183-60****+++
0.022	17.5	11.0	5.0	15.0	0.8	C822J223-60****+++
0.027	17.5	11.0	5.0	15.0	0.8	C822J273-60****+++
0.033	17.5	12.0	6.0	15.0	0.8	C822J333-60****+++

630Vdc(400Vac)						
容量 (μ F)	W	H	T	P	d	产品代码 Part number
0.039	17.5	12.0	6.0	15.0	0.8	C822J393-60****+++
0.047	17.5	12.0	6.0	15.0	0.8	C822J473-60****+++
0.056	17.5	13.5	7.5	15.0	0.8	C822J563-60****+++
0.068	17.5	14.5	8.5	15.0	0.8	C822J683-60****+++
0.082	17.5	14.5	8.5	15.0	0.8	C822J823-60****+++
0.10	17.5	16.0	10.0	15.0	0.8	C822J104-60****+++
0.12	17.5	19.0	11.0	15.0	0.8	C822J124-60****+++
0.047	26.5	15.0	6.0	22.5	0.8	C822J473-90****+++
0.056	26.5	15.0	6.0	22.5	0.8	C822J563-90****+++
0.068	26.5	15.0	6.0	22.5	0.8	C822J683-90****+++
0.082	26.5	15.0	6.0	22.5	0.8	C822J823-90****+++
0.10	26.5	15.0	6.0	22.5	0.8	C822J104-90****+++
0.12	26.5	16.0	7.0	22.5	0.8	C822J124-90****+++
0.15	26.5	17.0	8.5	22.5	0.8	C822J154-90****+++
0.18	26.5	17.0	8.5	22.5	0.8	C822J184-90****+++
0.22	26.5	18.5	10.0	22.5	0.8	C822J224-90****+++
0.27	26.5	22.0	12.0	22.5	0.8	C822J274-90****+++
0.33	26.5	22.0	12.0	22.5	0.8	C822J334-90****+++
0.39	26.5	22.0	12.0	22.5	0.8	C822J394-90****+++
0.15	32.0	18.0	9.0	27.5	0.8	C822J154-B0****+++
0.18	32.0	18.0	9.0	27.5	0.8	C822J184-B0****+++
0.22	32.0	18.0	9.0	27.5	0.8	C822J224-B0****+++
0.27	32.0	18.0	9.0	27.5	0.8	C822J274-B0****+++
0.33	32.0	20.0	11.0	27.5	0.8	C822J334-B0****+++
0.39	32.0	20.0	11.0	27.5	0.8	C822J394-B0****+++
0.47	32.0	22.0	13.0	27.5	0.8	C822J474-B0****+++
0.56	32.0	22.0	13.0	27.5	0.8	C822J564-B0****+++
0.68	32.0	24.5	15.0	27.5	0.8	C822J684-B0****+++
0.82	32.0	28.0	14.0	27.5	0.8	C822J824-B0****+++
1.0	32.0	33.0	18.0	27.5	0.8	C822J105-B0****+++
1.2	32.0	33.0	18.0	27.5	0.8	C822J125-B0****+++

备注: 1. “-”表示容量偏差。“-”=capacitance tolerance code, M= $\pm 20\%$, K= $\pm 10\%$, J= $\pm 5\%$, H= $\pm 3\%$, G= $\pm 2\%$
 2. “****”表示引线加工和包装代码(见table 1)。“****”=lead form and packaging code(refer to table 1)



C82
MMKP82 series

POWER SKY (H.K.) LTD.

■ 续 Continued

1 000Vdc(600Vac)						
容量 (μ F)	W	H	T	P	d	产品代码 Part number
0.00047	10.5	9.0	4.0	7.5	0.6	C823A471-30****+3
0.00056	10.5	9.0	4.0	7.5	0.6	C823A561-30****+3
0.00068	10.5	9.0	4.0	7.5	0.6	C823A681-30****+3
0.00082	10.5	9.0	4.0	7.5	0.6	C823A821-30****+3
0.0010	10.5	9.0	4.0	7.5	0.6	C823A102-30****+3
0.0012	10.5	11.0	5.0	7.5	0.6	C823A122-30****+3
0.0015	10.5	11.0	5.0	7.5	0.6	C823A152-30****+3
0.0018	10.5	11.0	5.0	7.5	0.6	C823A182-30****+3
0.0022	10.5	11.0	5.0	7.5	0.6	C823A222-30****+3
0.0027	10.5	12.0	6.0	7.5	0.6	C823A272-30****+3
0.0033	10.5	12.0	6.0	7.5	0.6	C823A332-30****+3
0.0010	13.0	9.0	4.0	10.0	0.6	C823A102-40****+3
0.0012	13.0	9.0	4.0	10.0	0.6	C823A122-40****+3
0.0015	13.0	9.0	4.0	10.0	0.6	C823A152-40****+3
0.0018	13.0	9.0	4.0	10.0	0.6	C823A182-40****+3
0.0022	13.0	9.0	4.0	10.0	0.6	C823A222-40****+3
0.0027	13.0	9.0	4.0	10.0	0.6	C823A272-40****+3
0.0033	13.0	9.0	4.0	10.0	0.6	C823A332-40****+3
0.0039	13.0	11.0	5.0	10.0	0.6	C823A392-40****+3
0.0047	13.0	11.0	5.0	10.0	0.6	C823A472-40****+3
0.0056	13.0	12.0	6.0	10.0	0.6	C823A562-40****+3
0.0068	13.0	12.0	6.0	10.0	0.6	C823A682-40****+3
0.0082	17.5	11.0	5.0	15.0	0.8	C823A822-60****+3
0.010	17.5	11.0	5.0	15.0	0.8	C823A103-60****+3
0.012	17.5	11.0	5.0	15.0	0.8	C823A123-60****+3
0.015	17.5	11.0	5.0	15.0	0.8	C823A153-60****+3
0.018	17.5	13.5	7.5	15.0	0.8	C823A183-60****+3
0.022	17.5	13.5	7.5	15.0	0.8	C823A223-60****+3
0.027	17.5	14.5	8.5	15.0	0.8	C823A273-60****+3
0.033	17.5	14.5	8.5	15.0	0.8	C823A333-60****+3
0.039	17.5	16.0	10.0	15.0	0.8	C823A393-60****+3
0.047	17.5	19.0	11.0	15.0	0.8	C823A473-60****+3
0.027	26.5	15.0	6.0	22.5	0.8	C823A273-90****+3
0.033	26.5	15.0	6.0	22.5	0.8	C823A333-90****+3
0.039	26.5	15.0	6.0	22.5	0.8	C823A393-90****+3
0.047	26.5	16.0	7.0	22.5	0.8	C823A473-90****+3
0.056	26.5	16.0	7.0	22.5	0.8	C823A563-90****+3
0.068	26.5	17.0	8.5	22.5	0.8	C823A683-90****+3
0.082	26.5	18.5	10.0	22.5	0.8	C823A823-90****+3
0.10	26.5	18.5	10.0	22.5	0.8	C823A104-90****+3
0.12	26.5	22.0	12.0	22.5	0.8	C823A124-90****+3
0.15	26.5	22.0	12.0	22.5	0.8	C823A154-90****+3
0.10	32.0	18.0	9.0	27.5	0.8	C823A104-B0****+3
0.12	32.0	20.0	11.0	27.5	0.8	C823A124-B0****+3
0.15	32.0	20.0	11.0	27.5	0.8	C823A154-B0****+3
0.18	32.0	22.0	13.0	27.5	0.8	C823A184-B0****+3
0.22	32.0	22.0	13.0	27.5	0.8	C823A224-B0****+3
0.27	32.0	24.5	15.0	27.5	0.8	C823A274-B0****+3
0.33	32.0	28.0	14.0	27.5	0.8	C823A334-B0****+3
0.39	32.0	33.0	18.0	27.5	0.8	C823A394-B0****+3
0.47	32.0	33.0	18.0	27.5	0.8	C823A474-B0****+3

1 600Vdc(650Vac)#						
容量 (μ F)	W	H	T	P	d	产品代码 Part number
0.00068	17.5	11.0	5.0	15.0	0.8	C823C681-60****+3
0.00082	17.5	11.0	5.0	15.0	0.8	C823C821-60****+3
0.0010	17.5	11.0	5.0	15.0	0.8	C823C102-60****+3
0.0012	17.5	11.0	5.0	15.0	0.8	C823C122-60****+3
0.0015	17.5	11.0	5.0	15.0	0.8	C823C152-60****+3
0.0018	17.5	11.0	5.0	15.0	0.8	C823C182-60****+3
0.0022	17.5	11.0	5.0	15.0	0.8	C823C222-60****+3
0.0027	17.5	11.0	5.0	15.0	0.8	C823C272-60****+3
0.0033	17.5	11.0	5.0	15.0	0.8	C823C332-60****+3
0.0039	17.5	11.0	5.0	15.0	0.8	C823C392-60****+3
0.0047	17.5	11.0	5.0	15.0	0.8	C823C472-60****+3
0.0056	17.5	11.0	5.0	15.0	0.8	C823C562-60****+3
0.0068	17.5	11.0	5.0	15.0	0.8	C823C682-60****+3
0.0082	17.5	12.0	6.0	15.0	0.8	C823C822-60****+3
0.010	17.5	12.0	6.0	15.0	0.8	C823C103-60****+3
0.012	17.5	13.5	7.5	15.0	0.8	C823C123-60****+3
0.015	17.5	13.5	7.5	15.0	0.8	C823C153-60****+3
0.018	17.5	14.5	8.5	15.0	0.8	C823C183-60****+3
0.022	17.5	14.5	8.5	15.0	0.8	C823C223-60****+3
0.027	17.5	16.0	10.0	15.0	0.8	C823C273-60****+3
0.033	17.5	19.0	11.0	15.0	0.8	C823C333-60****+3
0.015	26.5	15.0	6.0	22.5	0.8	C823C153-90****+3
0.018	26.5	15.0	6.0	22.5	0.8	C823C183-90****+3
0.022	26.5	15.0	6.0	22.5	0.8	C823C223-90****+3
0.027	26.5	15.0	6.0	22.5	0.8	C823C273-90****+3
0.033	26.5	16.0	7.0	22.5	0.8	C823C333-90****+3
0.039	26.5	17.0	8.5	22.5	0.8	C823C393-90****+3
0.047	26.5	18.5	10.0	22.5	0.8	C823C473-90****+3
0.056	26.5	18.5	10.0	22.5	0.8	C823C563-90****+3
0.068	26.5	22.0	12.0	22.5	0.8	C823C683-90****+3
0.082	26.5	22.0	12.0	22.5	0.8	C823C823-90****+3
0.039	32.0	18.0	9.0	27.5	0.8	C823C393-B0****+3
0.047	32.0	18.0	9.0	27.5	0.8	C823C473-B0****+3
0.056	32.0	18.0	9.0	27.5	0.8	C823C563-B0****+3
0.068	32.0	18.0	9.0	27.5	0.8	C823C683-B0****+3
0.082	32.0	20.0	11.0	27.5	0.8	C823C823-B0****+3
0.10	32.0	20.0	11.0	27.5	0.8	C823C104-B0****+3
0.12	32.0	22.0	13.0	27.5	0.8	C823C124-B0****+3
0.15	32.0	24.5	15.0	27.5	0.8	C823C154-B0****+3
0.18	32.0	24.5	15.0	27.5	0.8	C823C184-B0****+3
0.22	32.0	33.0	18.0	27.5	0.8	C823C224-B0****+3
0.27	32.0	33.0	18.0	27.5	0.8	C823C274-B0****+3
0.33	32.0	33.0	18.0	27.5	0.8	C823C334-B0****+3

2 000Vdc(700Vac)						
容量 (μ F)	W	H	T	P	d	产品代码 Part number
0.00022	17.5	11.0	5.0	15.0	0.8	C823D221-60****+3
0.00027	17.5	11.0	5.0	15.0	0.8	C823D271-60****+3
0.00033	17.5	11.0	5.0	15.0	0.8	C823D331-60****+3
0.00039	17.5	11.0	5.0	15.0	0.8	C823D391-60****+3
0.00047	17.5	11.0	5.0	15.0	0.8	C823D471-60****+3
0.00056	17.5	11.0	5.0	15.0	0.8	C823D561-60****+3
0.00068	17.5	11.0	5.0	15.0	0.8	C823D681-60****+3
0.00082	17.5	11.0	5.0	15.0	0.8	C823D821-60****+3
0.0010	17.5	11.0	5.0	15.0	0.8	C823D102-60****+3
0.0012	17.5	11.0	5.0	15.0	0.8	C823D122-60****+3
0.0015	17.5	11.0	5.0	15.0	0.8	C823D152-60****+3
0.0018	17.5	11.0	5.0	15.0	0.8	C823D182-60****+3
0.0022	17.5	11.0	5.0	15.0	0.8	C823D222-60****+3
0.0027	17.5	11.0	5.0	15.0	0.8	C823D272-60****+3
0.0033	17.5	12.0	6.0	15.0	0.8	C823D332-60****+3
0.0039	17.5	12.0	6.0	15.0	0.8	C823D392-60****+3
0.0047	17.5	12.0	6.0	15.0	0.8	C823D472-60****+3
0.0056	17.5	13.5	7.5	15.0	0.8	C823D562-60****+3
0.0068	17.5	13.5	7.5	15.0	0.8	C823D682-60****+3
0.0082	17.5	14.5	8.5	15.0	0.8	C823D822-60****+3
0.010	17.5	16.0	10.0	15.0	0.8	C823D103-60****+3
0.012	17.5	16.0	10.0	15.0	0.8	C823D123-60****+3
0.015	17.5	19.0	11.0	15.0	0.8	C823D153-60****+3
0.0010	26.5	15.0	6.0	22.5	0.8	C823D102-90****+3
0.0012	26.5	15.0	6.0	22.5	0.8	C823D122-90****+3
0.0015	26.5	15.0	6.0	22.5	0.8	C823D152-90****+3
0.0018	26.5	15.0	6.0	22.5	0.8	C823D182-90****+3
0.0022	26.5	15.0	6.0	22.5	0.8	C823D222-90****+3
0.0027	26.5	15.0	6.0	22.5	0.8	C823D272-90****+3
0.0033	26.5	15.0	6.0	22.5	0.8	C823D332-90****+3
0.0039	26.5	15.0	6.0	22.5	0.8	C823D392-90****+3
0.0047	26.5	15.0	6.0	22.5	0.8	C823D472-90****+3
0.0056	26.5	15.0	6.0	22.5	0.8	C823D562-90****+3
0.0068	26.5	15.0	6.0	22.5	0.8	C823D682-90****+3
0.0082	26.5	15.0	6.0	22.5	0.8	C823D822-90****+3
0.010	26.5	15.0	6.0	22.5	0.8	C823D103-90****+3
0.012	26.5	15.0	6.0	22.5	0.8	C823D123-90****+3
0.015	26.5	16.0	7.0	22.5	0.8	C823D153-90****+3
0.018	26.5	16.0	7.0	22.5	0.8	C823D183-90****+3
0.022	26.5	17.0	8.5	22.5	0.8	C823D223-90****+3
0.027	26.5	18.5	10.0	22.5	0.8	C823D273-90****+3
0.033	26.5	18.5	10.0	22.5	0.8	C823D333-90****+3
0.039	26.5	22.0	12.0	22.5	0.8	C823D393-90****+3
0.047	26.5	22.0	12.0	22.5	0.8	C823D473-90****+3
0.022	32.0	18.0	9.0	27.5	0.8	C823D223-B0****+3
0.027	32.0	18.0	9.0	27.5	0.8	C823D273-B0****+3
0.033	32.0	18.0	9.0	27.5	0.8	C823D333-B0****+3
0.039	32.0	20.0	11.0	27.5	0.8	C823D393-B0****+3
0.047	32.0	20.0	11.0	27.5	0.8	C823D473-B0****+3
0.056	32.0	22.0	13.0	27.5	0.8	C823D563-B0****+3
0.068	32.0	22.0	13.0	27.5	0.8	C823D683-B0****+3
0.082	32.0	24.5	15.0	27.5	0.8	C823D823-B0****+3
0.10	32.0	28.0	14.0	27.5	0.8	C823D104-B0****+3
0.12	32.0	33.0	18.0	27.5	0.8	C823D124-B0****+3
0.15	32.0	33.0	18.0	27.5	0.8	C823D154-B0****+3

备注: 1. “-”表示容量偏差。“-”=capacitance tolerance code, M=±20%,K=±10%,J=±5%,H=±3%,G=±2%
2. “****”表示引线加工和包装代码(见table 1)。“****”=lead form and packaging code(refer to table 1)